CONTRACT NO. C-22
COUNTY - LORAIN STA. 865+00 TO 1100+02.01
CUYAHOGA STA. 0+00 TO 5+00
DATE: APRIL 24, 1953

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

DESIGN SECTION D-7

CONTRACT NO. C-22

TURNPIKE CONSTRUCTION CONTRACT

STATION 865+00 TO STATION 5+00

U.S. GEOLOGICAL SURVEY QUADS.

LOCATION PLAN

TOTAL LENGTH OF CONTRACT = 23,602.01 L.F. = 4.470 M.

EQUATIONS { 1076+00 BACK = 1080+00 AHEAD
1100+02.01 BACK = 0+00 AHEAD

1 0 1 2

SCALE IN MILES

APPROVAL RECOMMENDED
KNAPPEN · TIPPETTS · ABBETT · McCARTHY
CONTRACTING ENGINEER
Jesse W. Stratton
11-6-53

APPROVED
J. E. GREINER CO.
CONSULTING ENGINEER
J. J. Jenkins Jr.
11-9-53

APPROVED
OHIO TURNPIKE COMMISSION
CHIEF ENGINEER
11-10-53

INDEX OF CONTRACT DRAWINGS

TITLE	SHEET NO.
COVER SHEET	1
INDEX SHEET	2
SUMMARY SHEET	3
SUMMARY SHEET (CONTINUED)	4
PLAN & PROFILE STA. 865 + 00 TO 889 + 00	5
PLAN & PROFILE STA. 889 + 00 TO 913 + 50	6
PLAN & PROFILE STA. 913 + 50 TO 941 + 00	7
PLAN & PROFILE STA. 941 + 00 TO 968 + 50	8
PLAN & PROFILE STA. 968 + 50 TO 996 + 00	9
PLAN & PROFILE STA. 996 + 00 TO 1023 + 00	10
PLAN & PROFILE STA. 1023 + 00 TO 1050 + 00	11
PLAN & PROFILE STA. 1050 + 00 TO 1081 + 00	12
PLAN & PROFILE STA. 1081 + 00 TO 5 + 00	13
RACE ROAD INTERSECTION PLAN & PROFILE	14
MADDOCK ROAD INTERSECTION PLAN & PROFILE	15
WOOSTER AVON LAKE ROAD STATE ROUTE 76 INTERSECTION PLAN & PROFILE	16
ROOT ROAD, INTERSECTION PLAN & PROFILE	17
BEREA ROAD INTERSECTION PLAN & PROFILE	18
INTERCHANGE KEY PLAN STATE ROUTE 10	19
INTERCHANGE GENERAL PLAN-STATE ROUTE 10	20
INTERCHANGE DETAIL PLAN - STATE ROUTE 10	21
INTERCHANGE DETAIL PLAN - STATE ROUTE 10	21A
RAMP R3, REVISED ALIGNMENT	22-23
INTERCHANGE DETAIL PLAN - STATE ROUTE 10	24
INTERCHANGE DETAIL PLAN - STATE ROUTE 10	25
INTERCHANGE PROFILES-RAMPS	26
INTERCHANGE PROFILES-RAMPS	27
INTERCHANGE PROFILES-RAMPS	28
DOUBLE BARREL 18' x 7' R. C. BOX CULVERT - MADDOCK RD. STA. 0 - (0 + 23)	29
DOUBLE BARREL 18' x 7' R. C. BOX CULVERT - TURNPIKE STA. 914 + 70	30
SINGLE BARREL 12' x 5' R. C. BOX CULVERT - TURNPIKE STA. 933 + 40	31
DOUBLE BARREL 14' x 6' R. C. BOX CULVERT - TURNPIKE STA. 993 + 51	32
SINGLE BARREL 16' x 6' R. C. BOX CULVERT - TURNPIKE STA. 1097 + 00	33
RACE ROAD BRIDGE - GENERAL PLAN AND SECTIONS	34
RACE ROAD BRIDGE - FRAMING PLAN AND SECTIONS	35
RACE ROAD BRIDGE - ABUTMENTS	36
MADDOCK ROAD BRIDGE - GENERAL PLAN AND SECTIONS	37
MADDOCK ROAD BRIDGE - FRAMING PLAN AND SECTIONS	38
MADDOCK ROAD BRIDGE - ABUTMENTS	39
WOOSTER - AVON LAKE ROAD BRIDGE - GENERAL PLAN AND SECTIONS	40
WOOSTER - AVON LAKE ROAD BRIDGE - FRAMING PLAN AND SECTIONS	41
WOOSTER - AVON LAKE ROAD BRIDGE - ABUTMENTS	42
ROOT ROAD BRIDGE - GENERAL PLAN AND SECTIONS	43
ROOT ROAD BRIDGE - FRAMING PLAN AND SECTIONS	44
ROOT ROAD BRIDGE - ABUTMENTS	45
CHESTNUT RIDGE ROAD BRIDGE - GENERAL PLAN AND SECTIONS	46
CHESTNUT RIDGE ROAD BRIDGE - FRAMING PLAN AND SECTIONS	47
CHESTNUT RIDGE ROAD BRIDGE - N. W. AND N. E. ABUTMENTS	48
CHESTNUT RIDGE ROAD BRIDGE - S. W. AND S. E. ABUTMENTS	49
CHESTNUT RIDGE ROAD BRIDGE - PIERS	50
TURNPIKE OVER ROUTE 10 RAMP - GENERAL PLAN AND SECTIONS	51
TURNPIKE OVER ROUTE 10 RAMP - FRAMING PLAN AND SECTIONS	52
TURNPIKE OVER ROUTE 10 RAMP - N. W. AND N. E. ABUTMENTS	53
TURNPIKE OVER ROUTE 10 RAMP - S. W. AND S. E. ABUTMENTS	54
TURNPIKE OVER ROUTE 10 RAMP - PIERS	55
TURNPIKE OVER ROUTE 10 - GENERAL PLAN AND SECTIONS	56
TURNPIKE OVER ROUTE 10 - FRAMING PLAN AND SECTIONS	57
TURNPIKE OVER ROUTE 10 - N. W. AND N. E. ABUTMENTS	58
TURNPIKE OVER ROUTE 10 - S. W. AND S. E. ABUTMENTS	59
TURNPIKE OVER ROUTE 10 - PIERS	60
ROUTE 10 RAMP OVER CHESTNUT RIDGE ROAD - GENERAL PLAN AND SECTIONS	61
ROUTE 10 RAMP OVER CHESTNUT RIDGE ROAD - FRAMING PLAN AND SECTIONS	62
ROUTE 10 RAMP OVER CHESTNUT RIDGE ROAD - ABUTMENTS	63
ROUTE 10 RAMP OVER CHESTNUT RIDGE ROAD - PIERS	64
RAMP OVER ROUTE 10 - GENERAL PLAN AND SECTIONS	65
RAMP OVER ROUTE 10 - FRAMING PLAN AND SECTIONS	66
RAMP OVER ROUTE 10 - ABUTMENTS	67
RAMP OVER ROUTE 10 - PIERS	68
MAIN LINE BRIDGE - NEW YORK CENTRAL SYSTEM - GENERAL PLAN AND SECTIONS	69
MAIN LINE BRIDGE - NEW YORK CENTRAL SYSTEM - FRAMING PLAN AND SECTIONS	70
MAIN LINE BRIDGE - NEW YORK CENTRAL SYSTEM - DETAILS	71
MAIN LINE BRIDGE - NEW YORK CENTRAL SYSTEM - ABUTMENTS	72
MAIN LINE BRIDGE - NEW YORK CENTRAL SYSTEM - PIERS	73
BEREA ROAD BRIDGE - GENERAL PLAN AND SECTIONS	74
BEREA ROAD BRIDGE - FRAMING PLAN AND SECTIONS	75
BEREA ROAD BRIDGE - ABUTMENTS	76
RACE, MADDOCK, WOOSTER-AVON LAKE, ROOT AND BEREA BRIDGES - PIERS	77
RACE, MADDOCK, WOOSTER-AVON LAKE, ROOT AND BEREA BRIDGES - DETAILS	78
SINGLE BARREL 10' x 5' R.C. BOX CULVERT STATE ROUTE 10 STA. 23 + 89.7	

SUPERELEVATION ROTATED ABOUT CENTER LINE OF PAVEMENT

SKETCH SHOWING TRAFFIC DETOURS AND TEMPORARY RUNAROUNDS

NOTE ① TRAFFIC ON RACE RD. TO BE REROUTED VIA A TEMPORARY RUNAROUND LOCATED EAST OF THE EXISTING RACE RD. DURING THE CONSTRUCTION OF RACE RD. BRIDGE.

NOTE ② TRAFFIC ON MADDOCK RD. TO BE REROUTED VIA A TEMPORARY RUNAROUND LOCATED EAST OF EXISTING MADDOCK RD. DURING THE CONSTRUCTION OF MADDOCK RD. BRIDGE.

NOTE ③ TRAFFIC ON WOOSTER AVON LAKE RD. TO BE REROUTED VIA A TEMPORARY RUNAROUND LOCATED EAST OF EXISTING WOOSTER AVON LAKE RD. DURING THE CONSTRUCTION OF THE WOOSTER AVON LAKE RD. BRIDGE.

NOTE ④ TRAFFIC ON ROOT RD. TO BE REROUTED VIA A TEMPORARY RUNAROUND LOCATED EAST OF EXISTING ROOT RD. DURING THE CONSTRUCTION OF THE ROOT RD. BRIDGE.

NOTE ⑤ TRAFFIC TO BE MAINTAINED ON CHESTNUT RIDGE RD. DURING THE CONSTRUCTION OF THE TURNPIKE BRIDGE SPANNING THE EXISTING CHESTNUT RIDGE RD.

NOTE ⑥ RECONSTRUCTION OF LORAIN RD. (STATE ROUTE 10) AND CONSTRUCTION OF TURNPIKE BRIDGE OVER LORAIN RD. AND BRIDGE SPANNING TURNPIKE RAMP OVER LORAIN ROAD TO TAKE PLACE UNDER TRAFFIC.

NOTE ⑦ CONSTRUCTION OF TURNPIKE BRIDGE OVER MAIN LINE OF NEW YORK CENTRAL SYSTEM TO TAKE PLACE WITHOUT INTERRUPTION TO RAILROAD TRAFFIC ON THIS LINE.

NOTE ⑧ TRAFFIC ON BEREA RD. TO BE REROUTED VIA A TEMPORARY RUNAROUND LOCATED NORTHWEST OF EXISTING BEREA RD. DURING CONSTRUCTION OF THE BEREA RD. BRIDGE.

REFERENCE TO SPECIFICATIONS:

THIS PROJECT SHALL BE CONSTRUCTED UNDER OHIO TURNPIKE PROJECT NO. 1, GENERAL SPECIFICATIONS, DATED DECEMBER 9, 1952

SPECIAL PROVISIONS FOR CONTRACT C-22

SUPPLEMENTAL	SPECIFICATION	A-5	DATED AUGUST	7, 1953
SUPPLEMENTAL	SPECIFICATION	B-20	DATED DECEMBER	9, 1952
SUPPLEMENTAL	SPECIFICATION	B-35	DATED DECEMBER	9, 1952
SUPPLEMENTAL	SPECIFICATION	T-10	DATED DECEMBER	9, 1952
SUPPLEMENTAL	SPECIFICATION	T-30	DATED DECEMBER	9, 1952
SUPPLEMENTAL	SPECIFICATION	T-35	DATED DECEMBER	9, 1952
SUPPLEMENTAL	SPECIFICATION	I-9	DATED DECEMBER	9, 1952
SUPPLEMENTAL	SPECIFICATION	I-16	DATED FEBRUARY	3, 1953
SUPPLEMENTAL	SPECIFICATION	I-30	REVISED JULY	9, 1953
SUPPLEMENTAL	SPECIFICATION	I-18	DATED MAY	28, 1953
SUPPLEMENTAL	SPECIFICATION	I-17	DATED MAY	28, 1953
SUPPLEMENTAL	SPECIFICATION	I-29	DATED MAY	28, 1953

NOTES:

ELEVATIONS REFER TO MEAN SEA LEVEL, U. S. COAST AND GEODETIC SURVEY. THE NORTH INDICATED AND REFERRED TO IS THE GRID NORTH OF THE NORTH ZONE OF THE OHIO STATE LAMBERT PROJECTION SYSTEM

PIPE LEGEND:

THE FOLLOWING SYMBOLS HAVE BEEN USED TO DESIGNATE THE VARIOUS PIPE TYPES USED.

SSRCCP	STANDARD STRENGTH REINFORCED CONCRETE CULVERT PIPE.
BCCMP	BITUMINOUS COATED CORRUGATED METAL PIPE.
PIBCCMP	PAVED INVERT BITUMINOUS COATED CORRUGATED METAL PIPE.
SSPCCP	STANDARD STRENGTH PLAIN CEMENT CONCRETE PIPE.
SRCSP	STANDARD REINFORCED CONCRETE SEWER PIPE.
EODT	EXTRA QUALITY DRAIN TILE.
SSVCP	STANDARD STRENGTH VITRIFIED CLAY PIPE.
ESVCP	EXTRA STRENGTH VITRIFIED CLAY PIPE.
WIP	WELDED WROUGHT IRON PIPE.

INDEX OF STANDARD DRAWINGS

TITLE	STANDARD DWG. NO.	DATED
TURNPIKE DITCH DETAILS	1	5- 6-53
STANDARD HEADWALLS-FOR PIPE SIZES 48" & UNDER	2	1-20-53
STANDARD HEADWALLS-FOR PIPE SIZES OVER 48"	3	1-20-53
TYPICAL ROADWAY SECTIONS	4	5- 6-53
HANDRAIL DETAILS	5	5- 6-53
INLETS AND CURBS	6	12-21-53
MANHOLES	7	5- 6-53
PAVEMENT REINFORCEMENT & DETAILS	8	10-20-53
TRANSVERSE PAVEMENT JOINTS, TYPE A	9	2- 7-53
TRANSVERSE PAVEMENT JOINTS, TYPE B	10	5- 6-53
PAVEMENT JOINT SPACING	11	12-31-52
RIGHT OF WAY FENCE & GATES	12	5- 6-53
RIGHT OF WAY FENCE INSTALLATION DETAILS	13	5- 6-53
PERMANENT BARRICADE, PERMANENT MONUMENT & DELINEATORS	14	3-18-54
DRAINAGE DETAILS FOR TURNPIKE OVERPASSES & UNDERPASSES	15	4-27-53
UNDERDRAINS	16	1-20-53
GUARD RAILS, TYPE A & TYPE B	17	1-24-53
GUARD RAILS, TYPE C & TYPE D	18	5- 6-53
AGRICULTURAL TILE DRAINAGE-TYPICAL DETAILS	19	12- 5-52
FLOOD GATES FOR RIGHT OF WAY FENCE	20	1- 6-53
TRANSVERSE PAVEMENT JOINTS, TYPE C	21	1-23-53
CULVERT PIPE BEDDING AND BACKFILL	22	2-19-53

LEGEND

NEW MANHOLE	EXISTING STORM OR SANITARY SEWER
NEW INLET	EXISTING WATER LINE
HYDRANT	BUILDINGS NOT TO BE DISTURBED
EXISTING MANHOLE	BUILDINGS WITHIN R.O.W. TO BE TORN DOWN OR MOVED
EXISTING CATCH BASIN OR INLET	EXISTING ROAD
MONUMENT	PROPOSED DRAINAGE DITCH
TEL. POLE	O.B.T. OHIO BELL TELEPHONE
POWER POLE	O.E. OHIO EDISON
COMB. TEL. & POWER POLE (JOINT)	C.E.I. CLEVELAND ELECTRIC ILLUMINATING CO.
WATER OR GAS VALVE	EXISTING GAS LINE
WATER OR GAS METER	GUARD RAIL

NO.	REVISION	BY	DATE
1	AS BUILT		7/15/56

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

INDEX SHEET

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: J. H. CHECKED: J. R. DATE: 4-27-53
DRAWN: J. H. IN CHARGE: E. F. G. SCALE:

CONTRACT NO. C-22 SHEET 1 OF 78

REFERENCE NUMBER	SPECIFICATION ITEM NUMBER	DESCRIPTION	UNIT	SHEET NUMBERS 4	5	6	7	8	9	10	11	12	13	14	15	16	17	19	20	21	22	23	24	28	29	30	31	32	78	TOTALS	PROPOSAL QUANTITIES
		ROADWAY																													
1	E-1	Roadway Excavation	C.Y.																												
2	E-4	Borrow	C.Y.																												
3	E-8	Removal and Disposal of Existing Pavement	S.Y.																												
4	E-11	Water	M Gal.																												
5	E-12	Pipe Removed - Under 16"	L.F.																												
6	E-12	Pipe Removed - 16" and Over	L.F.																												
7	I-12	Concrete Curb Type I	L.F.																												
8	I-12	Concrete Curb, Type II	L.F.																												
9	I-12	Combination Curb and Gutter, Type III	L.F.																												
10	I-12	Combination Curb and Gutter,																													
		Type III Modified "A"	L.F.																												
11	I-12	Combination Curb and Gutter,																													
		Type III Modified "B"	L.F.																												
12	I-13	Walks - 6" I-17 Side Approaches																													
		and Mail Box Turnouts	S.F.																												
13	I-15	Guard Rail, Type "A"	L.F.																												
14	I-15	Guard Rail, Type "B"	L.F.																												
15	I-15	Guard Rail, Type C-1 or C-2	L.F.																												
16	I-15	Guard Rail, Type D-3	L.F.																												
17	I-23	Right of Way Fence, Type II	L.F.																												
18	I-24	Delineators	Each																												
19	I-26	Permanent Monuments and																													
		Station Markers	Each																												
20	I-27	Classified Embankment Material	Cu.Yd.																												
21	I-28	Temporary Cattle Fence	L.F.																												
22	L-3	Placing Stockpiled Topsoil	S.Y.																												
23	L-3	Bonemeal and Rawbone	Ton																												
24	L-3	Organic Fertilizer	S.Y.																												
25	L-6	Roadside Cleanup	L.S.																												
26	L-9	Commercial Fertilizer, 8-16-8	Ton																												
27	L-9	Agricultural Hydrated Lime	Ton																												
28	L-9	Agricultural Ground Limestone	Ton																												
29	L-9	Bonemeal or Rawbone	Ton																												
30	L-9	Seeding and Protecting, Type A	S.Y.																												
31	L-19	Seeding and Mulching																													
		(special Seeding)	S.Y.																												
		DRAINAGE																													
34	E-2	Excavation for Structures	C.Y.																												
35	E-3	Channel Excavation	C.Y.																												
36	S-1	Concrete for Structures (Class C)	C.Y.																												
37	S-4	Reinforcing Steel	Lb.																												
38	S-27	Pipe for Roadway Culverts - 18" S.S.R.C.C.P.	L.F.																												
39	S-27	Pipe for Roadway Culverts - 24" S.S.R.C.C.P.	L.F.																												
40	S-27	Pipe for Roadway Culverts - 30" S.S.R.C.C.P.	L.F.																												
41	S-27	Pipe for Roadway Culverts - 36" S.S.R.C.C.P.	L.F.																												
42	S-27	Pipe for Roadway Culverts - 54" S.S.R.C.C.P.	L.F.																												
43	S-27	Pipe for Roadway Culverts - 60" S.S.R.C.C.P.	L.F.																												
44	S-27	Pipe for Roadway Culverts - 24" E.S.R.C.C.P.	L.F.																												
45	S-27	Pipe for Roadway Culverts - 42" E.S.R.C.C.P.	L.F.																												
46	I-1	Pipe for Driveways 15" S.S.R.C.C.P.	L.F.																												
47	I-1	Pipe for Driveways 18" S.S.R.C.C.P.	L.F.																												
48	I-2	Storm Sewers - 15" S.S.R.C.C.P.	L.F.																												
49	I-2	Storm Sewers - 18" S.S.R.C.C.P.	L.F.																												
50	I-2	Storm Sewers - 15" S.R.C.S.P. or S.S.V.C.P.	L.F.																												
33	I-2	Storm Sewers - 30" S.S.R.C.C.P.	L.F.																												
51	I-2	Storm Sewers - 24" S.S.R.C.C.P. or S.S.V.C.P.	L.F.																												
52	I-2	Storm Sewers - 36" S.R.C.S.P. or S.S.V.C.P.	L.F.																												
53	I-2	Storm Sewers - 78" S.R.C.S.P.	L.F.																												
54	I-2	Storm Sewers - 6" S.S.R.C.C.P. or S.S.V.C.P.	L.F.																												
55	I-2	Storm Sewers - 15" S.S.R.C.C.P. or S.S.V.C.P.	L.F.																												
56	I-2	Storm Sewers - 15" P.I.B.C.C.M.P. - 14 Ga.	L.F.																												
57	I-4	6" Pipe Underdrain, Type A	L.F.																												
58	I-5	Pipe Special - 6" S.S.R.C.C.P. - 1/16 Bend	Ea.																												
59	I-5	Pipe Special - 15" S.S.R.C.C.P. - 1/16 Bend	Ea.																												
60	I-5	Pipe Special - 15" B.C.C.M.P. - 1/16 Bend - 14 Ga.	Ea.																												
	I-1	Pipe for Driveways 18" C.M.P.	L.F.																												

REFERENCE NUMBER	SPECIFICATION ITEM NUMBER	DESCRIPTION	UNIT	SHEET NUMBERS 33	36	39	42	45	50	55	60	64	68	73	TOTALS	PROPOSAL QUANTITIES
		STRUCTURES														
91	E-2	Excavation for Structures (Dry)	C.Y.													
92	T-35	Asphaltic Concrete Surface														
		Course, Type C	C.Y.													
93	S-1	Concrete for Structures (Class C)	C.Y.													
94	S-3	Waterproofing - Type C	S.Y.													
95	S-4	Reinforcing Steel	Lb.													
96	S-7	Structural Steel	Lb.													
97	S-9	Structural Expansion and / or														
		Contraction Joints	Lb.													
98	S-14	Metal Hand Rail, Type A	L.F.													
99	S-14	Metal Hand Rail, Type B	L.F.													
100	S-16	First Test Pile	Ea.													
101	S-17	Pile Test Load	Ea.													
102	S-18	Furnishing Bearing Piles, Steel - 10BP42	L.F.													
103	S-18	Driving Bearing Piles - Steel - 10 BP42	L.F.													
104	S-18	Splices for Steel Bearing Piles - 10BP42	Ea.													
105	S-18	Furnishing Bearing Piles, Steel - 10BP53	L.F.													
106	S-18	Driving Bearing Piles - Steel - 12BP53	L.F.													
107	S-18	Splices for Steel Bearing Piles - 12BP53	Ea.													
108	S-19	Soil Load Bearing Test	Ea.													
109	S-29	Drainage of Structures - 6" Pipe	L.F.													
110	S-29	Drainage of Structures - 6" W.I. Pipe	L.F.													
111	S-29	Drainage of Structures - 8" Pipe	L.F.													
112	S-29	Drainage of Structures - Scuppers, Type A	Ea.													
113	S-29	Drainage of Structures - Scuppers, Type B	Ea.													
114	I-14	Paved Ditches - 6" Grouted Stone	S.Y.													
115	I-15	Guard Rail Type A	L.F.													
116	I-24	Delineators	Ea.													
		MISCELLANEOUS														
120	I-29	Construction Contract Information Signs	Ea.													
		Maintenance of Traffic	L.S.													
		Engineers Office Bldg's & Facilities	L.S.													

NOTE

SEE FINAL ESTIMATE AND RECAPITULATION OF QUANTITIES FOR CONTRACT SECTION C-22 FOR FINAL TOTAL QUANTITIES.

NO.	REVISION	BY	DATE
1	AS BUILT		10/8/56

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

SUMMARY SHEET

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: | CHECKED: J. R. | DATE: 4-27-53
DRAWN: J. T. | IN CHARGE: E.F.G. | SCALE:

CONTRACT NO. C-22 SHEET 2 OF 78

REFERENCE NUMBER	SPECIFICATION ITEM NUMBER	DESCRIPTION	UNIT	SHEET NUMBERS 4	5	6	7	8	9	10	11	12	13	14	15	16	17	19	20	21	22	23	24	28	29	30	31	32	78	TOTALS	PROPOSAL QUANTITIES
		DRAINAGE (cont'd)																													
61	I-8	Manholes, Type I	Ea.																												
62	I-8	Manholes, Type II	Ea.																												
63	I-8	Inlets, Type A	Ea.																												
64	I-8	Inlets, Type A-1	Ea.																												
65	I-8	Inlets, Type B	Ea.																												
66	I-9	Stone Underdrains No. 1	L.F.																												
67	I-10	Riprap, Type A	S.Y.																												
68	I-14	Paved Ditches-6" Grouted Stone	S.Y.																												
69	I-16	Catch Basins Abandoned	Ea.																												
70	I-30	Farm Tile Drains-6" EQDT	L.F.																												
71	I-30	Farm Tile Drains-8" EQDT	L.F.																												
72	I-30	Farm Tile Drains-10" EQDT	L.F.																												
73	I-30	Farm Tile Drains-12" EQDT	L.F.																												
74	I-30	6" Pipe Outlets for Tile Drains	L.F.																												
75	I-30	8" Pipe Outlets for Tile Drains	L.F.																												
76	I-30	10" Pipe Outlets for Tile Drains	L.F.																												
77	I-30	12" Pipe Outlets for Tile Drains	L.F.																												
		PAVEMENT																													
78	B-20	Waterbound Macadam Base Course-8"																													
		Laid in 2-4" Courses	S.Y.																												
79	B-20	Waterbound Macadam Base Course-5"	S.Y.																												
80	B-35	Asphaltic Concrete Base and/or Leveling																													
		Course	C.Y.																												
81	B-35	Sealing Vertical Face of Existing Pavement	L.F.																												
82																															
83	T-30	Bituminous Prime Coat-MC-0	Gal.																												
84	T-30	Bituminous Prime Coat-M5,7 Rt-2 or M5,7 Rt-3	Gal.																												
85	T-33	Bituminous Macadam Surface Course-3"	S.Y.																												
86	T-35	Asphaltic Concrete Surface Course Type A	C.Y.																												
87	T-71	Reinforced Portland Cement Concrete																													
		Pavement-10"	S.Y.																												
89	I-22	Selected Sub-base	C.Y.																												
90	I-17	Side Approaches and Mail Box Turnouts	C.Y.																												
	T-10	Traffic Compacted Surface Course 6"	C.Y.																												
	T-71	Reinforced Portland Cement Concrete																													
		Pavement-8"	S.Y.																												

NOTE

SEE FINAL ESTIMATE AND RECAPITULATION OF QUANTITIES FOR CONTRACT SECTION C-22 FOR FINAL TOTAL QUANTITIES.

NO.	REVISION	BY	DATE
1	AS BUILT		10/8/56

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

SUMMARY SHEET

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED:	CHECKED: T.K.	DATE: 4-27-53
DRAWN: J.R.	IN CHARGE E.F.G.	SCALE:

CONTRACT NO. C-22 SHEET 3 OF 78

For details of Chestnut Ridge Rd Bridge, Structure #5, see Sheets 45 to 49, incl.
For details of Route 10 Ramp over Chestnut Ridge Rd, Structure #6, see Sheets 60 to 63, incl.
For details of Turnpike Bridge over Route 10 Ramp, Structure #7, see Sheets 50 to 54, incl.
For details of Turnpike Bridge over Route 10, Structure #8, see Sheets 55 to 59, incl.

Notes:

For R.O.W. Fencing and Additional Drainage between Chestnut Ridge Road and Lorain Road see Sheets 20, 21, 22, 23 and 24.

Delineators shall be installed 100 ft. apart and 1 ft. from edge of paved shoulder. One series shall be adjacent to the outside 10 ft. shoulder of the north pavement from Sta. 1023+00 to Sta. 1028+00, from Sta. 1032+00 to Sta. 1042+00 and from Sta. 1043+00 to Sta. 1050+00. Another series shall be adjacent to the inside 8 ft. shoulder of the south pavement from Sta. 1023+00 to Sta. 1050+00.

Install Type A Guard Rail in accordance with Standard Drawing No. 17.

Install Type A Guard Rail on Left side of Turnpike between Sta. 1034+06 and Sta. 1036+53, and between Sta. 1041+57 and Sta. 1042+20 and on Right side of Turnpike between Sta. 1024+05 and Sta. 1024+60.

Install Type B Guard Rail on Right side of Turnpike between Sta. 1029+80 and Sta. 1034+92, and between Sta. 1047+50 and Sta. 1050+00.

For additional Guard Rail installations, see Interchange Detail Sheets 20, 21, 22, 23 and 24.

QUANTITIES

NO.	ITEM	LOCATION & REMARKS	UNIT	ESTIMATED QUANTITY	FINAL QUANTITY
	ROADWAY				
E-1	Roadway Excavation		Cu.Yd.	808	1,879
E-11	Water		M.Gal.	4.178	410
I-15	Guard Rail, Type A		Lin.Ft.	3,186	2922
I-15	Guard Rail, Type B		Lin.Ft.	245	762
I-24	Delineators		Ea.	39	43
I-26	Permanent Monuments & Station Markers		Ea.	1	1
L-3	Placing Stockpiled Topsoil		Sq.Yd.	11,197	11,951
	Commercial Fertilizer, 10-20-10	EW(RV)6	Ton	0	0.9
L-9	Agricultural Hydrated Lime		Ton	2	4.6
L-9	Seeding Type A	EW(RV)6	Sq.Yd.	0	11,095
L-9	Special Seeding	EW(RV)6	Sq.Yd.	0	14,665
	DRAINAGE				
E-2	Excavation for Structures		Cu.Yd.	297	449
E-3	Channel Excav.		Cu.Yd.	108	
S-1	Concrete for Structures Class C		Cu.Yd.	8.0	12.9
S-4	Reinforcing Steel		Lb.	370	550.4
S-27	Pipe for Roadway Culverts 42"-ES.R.C.C.P.		Lin.Ft.	288	292
I-2	Storm Sewers 15" SSRCCP		Lin.Ft.	518	501
I-5	Pipe Specials 1/16 Bends 15"-S.S.R.C.C.P.		Ea.	6	6
I-8	Inlets, Type B-Ave. Height + 6'		Ea.	3	3
I-8	Inlets, Type A-1 Ave. Height + 4'		Ea.	3	3
I-10	Riprap, Type A		Sq.Yd.	6	17.6
	PAVEMENT				
T-33	Bituminous Macadam Surface Course-3"		Sq.Yd.	7,040	8,449
T-71	Reinforced Portland Cement Concrete Pavement-10"		Sq.Yd.	12,070	12,106
T-22	Selected Sub-Base		Cu.Yd.	5,560	6932.3
	Plug Gas Well	EW(FA)1	Ea.	0	

NOTE: Quantities shown are for Turnpike proper only

NO.	REVISION	BY	DATE
	MICROWAVE CABLE	JHF	5-21-85
2	U.S. RTE 20 BRIDGE	D.F.C.	8-17-82
△	AS BUILT		

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

PLAN AND PROFILE
LORAIN COUNTY
STA. 1023+00 TO STA. 1050+00

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: R.A.O. DRAWN: K.K. CHECKED: J.L.R. IN CHARGE: E.F.G. DATE: 4-27-81 SCALE: AS NOTED

CONTRACT NO. C- 22 SHEET 10 OF 78

NO.	REVISION	BY	DATE
1	AS BUILT		10/5/56

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

INTERCHANGE
KEY PLAN
STATE ROUTE 10
LORAIN COUNTY

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: A.M.	CHECKED: E.F.G.	DATE: 4-27-53
DRAWN: J.E.L.	IN CHARGE: W.M.H.	SCALE: 1IN=150 FT.

CONTRACT NO. C-22 SHEET 18 OF 78

R.O.W. LEGEND

TURNPIKE R.O.W. (NO FENCING REQUIRED)

TURNPIKE R.O.W. (FENCING REQUIRED)

TURNPIKE FENCING (NOT R.O.W.)

QUANTITIES

NO.	ITEM	LOCATION & REMARKS	UNIT	ESTIMATED QUANTITY	FINAL QUANTITY
	ROADWAY				
E-1	Roadway Excavation		Cu.Yd.	15,[illegible]	16,64[illegible]
E-1	Rdwy. Excav.	Unsuitable Mat'l (RT. 10)	Cu.Yd.		218.3
E-11	Water		M.Gal.	3,018	911
I-23	Right of Way Fence, Type 2		Lin.Ft.	6,820	6907
L-9	Commercial Fertilizer 10-20-10	EW(RV)6	Ton	0	1.5
L-9	Agricultural Hydrated Lime		Ton	2.5	7.7
L-9	Seeding Type A	EW(RV)6	S.Y.	0	19,717
L-19	Special Seeding	EW(RV)6	S.Y.	0	3[illegible],651

NO.	REVISION	BY	DATE
1	AS BUILT		

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

INTERCHANGE GENERAL PLAN

STATE ROUTE 10
LORAIN COUNTY

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED A.M.	CHECKED E.F.G.	DATE 4-27-53
DRAWN J.E.L.	IN CHARGE W.M.H.	SCALE 1" = 150'

CONTRACT NO. C-22 SHEET 19 OF 78

QUANTITIES

NO.	ITEM	LOCATION & REMARKS	UNIT	ESTIMATED QUANTITY	FINAL QUANTITY
	ROADWAY				
I-5	Guard Rail Type B		L.Ft.	0	10
I-12	Concrete Curb, Type I		Lin. Ft.	1150	1150
I-12	Concrete Curb, Type II		Lin. Ft.	1004	1005
I-12	Combination Curb and Gutter, Type III		Lin. Ft.	2038	2045
I-15	Guard Rail, Type A		Lin. Ft.	615	1009
I-15	Guard Rail, Type C1 or C-2		Lin. Ft.	5279	4842
I-3	Placing Stockpiled Topsoil		Sq. Yd.	3527	5152
I-15	Guard Rail Type D-3		Lin. Ft.	0	48
	DRAINAGE				
E-2	Excavation for Structures		Cu. Yd.	960	626.20
E-3	Channel Excavation		Cu. Yd.	15	0
S-1	Concrete for Structures (Class C)		Cu. Yd.	27.4	26.4
S-4	Reinforcing Steel		Lbs.	1329	1514.4
I-2	Storm Sewers 15" SSPCCP		Lin. Ft.	776	785.2
I-2	Storm Sewers 13" SSRCCP		Lin. Ft.	148	140.4
I-30	Pipe Outlet for Tile Drain 12" CMP		L.Ft.		10
S-27	Pipe for Roadway Culverts 24" ES RCCP		Lin. Ft.	500	524.7
I-2	9" Sewers - 6" SS RCCP		Lin. Ft.	180	177
S-27	Pipe for Roadway Culverts 36" SS RCCP		Lin. Ft.	76	89.5
I-5	Pipe Trans. 42" RCCP & Bell		Each	2	1
I-2	Storm Sewers 15" PIBCCMP		Lin. Ft.	432	401.1
I-5	Pipe Specials - 16 Bends 15" BCCMP		Ea.	8	11
I-8	Manholes Type I Ave. Height = 6'		Ea.	1	1
I-8	Manholes Types II Ave. Height = 22'		Ea.	1	1
I-8	Inlets, Type A Ave. Height = 4.5		Ea.	1	1
I-8	Inlets, Type B Ave. Height = 4.5		Ea.	13	13
I-14	Paved Ditches	Stone & Grout - 6"	Sq. Yd.	39	76.4
	PAVEMENT				
T-33	Bituminous Macadam Surface Course 3"		Sq. Yd.	4138	3,950
T-71	Reinforced Portland Cement Concrete Pavement - 10"		Sq. Yd.	7702	7740
I-22	Selected Sub-base		Cu. Yd.	6484	3,245

NO.	REVISION	BY	DATE
1	As Built		

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

INTERCHANGE DETAIL PLAN

STATE ROUTE 10
LORAIN COUNTY

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: A.M.	CHECKED: E.F.G.	DATE: 4-27-53
DRAWN: T.F.	IN CHARGE: W.M.H.	SCALE: 1 IN. = 50 FT.

CONTRACT NO. C-22 SHEET 21 OF 78

Install Type A Guard Rail, Pier Protection for Center Piers only at center of Rt. 10 under Structure 8 (300 Lin. Ft.)

NOTES:

INSTALL TYPE A GUARD RAIL AS FOLLOWS:

Right of R5: Sta. 23+98 to Sta. 25+46
Right of R5: Sta. 27+49 to Sta. 30+50
Right of R4: Sta. 4+06 to Sta. 9+18
Right of R4: Sta. 11+15 to Sta. 12+15

INSTALL TYPE C-1 OR C-2 GUARD RAIL AS FOLLOWS:

Right of R4: Sta. 12+15 to Sta. 13+00

Install Type III Combination Curb and Gutter from Sta. 12+42.87 to Sta. 13+00 on Right of R4

For R.O.W. and Fencing, see Sheet # 19.

For additional Drainage Details, see Sheets 10 and 11

QUANTITIES

NO.	ITEM	LOCATION & REMARKS	UNIT	ESTIMATED QUANTITY	FINAL QUANTITY
	ROADWAY				
I-12	Combination Curb and Gutter, Type III		Lin. Ft.	57	83
I-15	Guard Rail, Type A		Lin. Ft.	965	1361
I-15	Guard Rail, Type C-1 or C-2		Lin. Ft.	185	85
L-3	Placing Stockpiled Topsoil		Sq. Yd.	753	715
	DRAINAGE				
E-2	Excavation for Structures		Cu. Yd.	160	6.0
S-1	Concrete for Structures (Class C)		Cu. Yd.	1.5	1.6
S-4	Reinforcing Steel		Lbs.	90	111.7
I-2	Storm Sewers 15" SSRCCP		Lin. Ft.	342	335.5
I-10	Rip Rap Type A		Sq. Yd.		39.6
	PAVEMENT				
T-33	Bituminous Macadam Surface Course-3"		Sq. Yd.	1240	97 see sht. 10
T-71	Reinforced Portland Cement Concrete Pavement-10"		Sq. Yd.	1147	1152
I-22	Selected Sub-base		Cu. Yd.	817	185

NO.	REVISION	BY	DATE
1	AS BUILT		10-8-56

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

INTERCHANGE DETAIL PLAN
STATE ROUTE 10
LORAIN COUNTY

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: A. M. | CHECKED: E. F. G. | DATE: 4-10-53
DRAWN: T. F. | IN CHARGE: W. M. H. | SCALE: 1 IN. = 50 FT.

CONTRACT NO. C- 22 SHEET 22 OF 78

PLAN

SCALE: 1 IN. = 20 FT

PROFILE-ROUTE 10 RAMP

SCALE: VERT. 1 IN. = 2 FT.
HORIZ. 1 IN. = 50 FT.

LOCATION PLAN

SCALE 1 IN. = 500 FT.

GENERAL NOTES

Design in accordance with Design Specifications for Highway Structures, State of Ohio, Oct. 1, 1951.
Predicted frequency per lane of 2000.
Superstructure: Concrete Slab on WF stringers.
Substructure: Piers - concrete bents on steel bearing piles.
Abutments on steel bearing piles.
All elevations refer to Mean Sea Level Datum as established by U.S. Coastal and Geodetic survey.
For details of borings, see Master Soil Profile, Contract C-22, and respective laboratory logs in book entitled "Ohio Turnpike Project No. 1 Subsurface Exploration Logs, Contract C-22."

TRANSVERSE SECTION WEST BOUND ROADWAY

SCALE: 1 IN. = 10 FT.

TRANSVERSE SECTION EAST BOUND ROADWAY

SCALE: 1 IN. = 10 FT.

ELEVATION

SCALE: 1 IN. = 20 FT.

LONGITUDINAL SECTION

SCALE: 1 IN. = 20 FT.

SUMMARY OF QUANTITIES

ITEM No.	DESCRIPTION	UNIT	ABUT.	PIERS.	SUPERSTR.	GENERAL	TOTAL.
E-2	Excavation for structures	Cu. Yd.	415.1	435.0			850.1
S-1	Concrete for structures - Class C	Cu. Yd.	353.5	433.6	295.7		1082.8
S-4	Reinforcing Steel	Pounds	62,796.5	117,471.3	45,606.8		225,874.6
S-7	Structural Steel	Pounds			196,810		196,810
S-9	Structural Expansion Joints, and/or Contraction Joints	Pounds			16,678		16,678
S-14	Railing Type A	L.F.			510.1		510.1
S-16	First Test Pile	Each	1				1
S-17	Pile Test Load	Each					0
S-18	Furnishing Steel Bearing Piles 10BP42	L.F.				5491	5491
S-18	Driving Steel Bearing Piles "	L.F.				4670.4	4670.4
S-18	Splices for Steel Bearing Piles "	Each					0
S-29	Drainage of Structure - Scupper Type A	Each			3		3
S-29	Drainage of Structure - 6" W.I. Pipe	L.F.				84.4	84.4
S-29	Drainage of Structure - 6" Pipe	L.F.				180	180
I-15	Guard Rail - Type A	L.F.			507.3		507.3
I-24	Delineators	Each			2		2

STRUCTURE NO. 7

REFERENCE DRAWINGS

Framing Plan	Sheet 51.
Abutments	Sheets 52 & 53.
Piers	Sheet 54.
Handrail Details	Std. Dwg. No. 5.
Drainage Details	Std. Dwg. No. 15.
Guard Rail Details	Std. Dwg. No. 17.
Roadway Joints	Sheet 51.

NO.	REVISION	BY	DATE
2	Deck Replacement & Widening, See RMP 43-24-10		1984
1	As Built		10-8-56

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER ROUTE 10 RAMP - GENERAL PLAN & SECTIONS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A. | CHECKED: I.E., A.A. | DATE: 4-24-53
DRAWN: J.B.B. | IN CHARGE: O.A. | SCALE: AS NOTED

CONTRACT NO. C-22 SHEET 50 OF 78

FRAMING PLAN

NO SCALE

SECTION A-A

DECK CROSS SECTION WEST BOUND LANE

SCALE: 1/2 IN. = 1 FT.

SECTION B-B

DECK CROSS SECTION EAST BOUND LANE

SCALE: 1/2 IN. = 1 FT.

DETAIL OF EXPANSION ABUTMENT

SCALE: 1/2 IN. = 1 FT.

DETAIL OF FIXED & EXPANSION PIER

SCALE: 1/2 IN. = 1 FT.

DETAIL OF WEB SPLICE

SCALE: 1/2 IN. = 1 FT.

CAMBER DIAGRAM FOR STRINGERS

FOR DEAD LOAD

PARAPET - DETAIL

SCALE: 3/4 IN. = 1 FT.

ROADWAY EXPANSION JOINT AT ABUTMENT

SCALE: 1 IN. = 1 FT.

NOTES

For General Notes see Sheet 50
For Structural Steel Notes see Sheet 34
For Concrete Notes see Sheet 35

NO.	REVISION	BY	DATE
2	DECK REPLACEMENT & WIDENING, SEE RAMP-43-84-10	—	1984
1	AS BUILT		10/8/56

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER RT. 10 RAMP

FRAMING PLAN

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O. A. CHECKED: I. E., A. A. DATE: 4-24-53
DRAWN: W. A. IN CHARGE: O. A. SCALE: AS NOTED

STRUCTURE NO. 7

CONTRACT NO. C-22 SHEET 51 OF 78

PLAN
SLAB REMOVED
NORTHWEST ABUTMENT (AS SHOWN)
NORTHEAST ABUTMENT (TO OPP. HAND)

SCALE: 1/4"=1'-0"

SECTION B-B
SCALE: 3/8"=1'-0"

NOTE:
N.W.A. denotes Northwest Abutment
N.E.A. denotes Northeast Abutment

NOTE:
SECT. B-B IS NORMAL TO RAMP-R-2

SLAB PLAN
SCALE: 1/4"=1'-0"

NOTE:
FOR PARAPET REINFORCING SEE SHEET No. 51

END ELEVATION
SCALE: 3/8"=1'-0"

SECTION A-A
SCALE: 3/8"=1'-0"

SECTION C-C
SCALE: 1/4"=1'-0"

FRONT ELEVATION
SCALE: 1/4"=1'-0"

Pile No.	Pile Tip Elevations NW. Abut.	NE. Abut.
1	748.30	753.14
2	748.28	753.02
3	746.47	753.14
4	752.24	753.11
5	749.30	753.14
6	749.74	752.94
7	746.80	751.72
8	749.89	753.35
9	749.80	752.81
10	749.75	753.83
11	750.50	746.83
12	751.00	748.58
13	750.50	750.83
14	751.00	751.92

PILE PLAN
SCALE: 1/8"=1'-0"

NOTES
For General Notes, see Sheet 50.
For Concrete Notes, see Sheet 35.
Max. Pile Load = 40 Tons

STRUCTURE NO. 7

NO.	REVISION	BY	DATE
2	Deck Replacement & Widening, See RMP-43-84.10		1984
1	AS BUILT		10/8/86

OHIO TURNPIKE COMMISSION
OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER RT. 10 RAMP
N.W. & N.E. ABUTMENTS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A.	CHECKED: I.E. & A.A.	DATE: 4-24-53
DRAWN: A.T. Vaccarello	IN CHARGE O.A.	SCALE: AS NOTED

CONTRACT NO. C-22 SHEET 52 OF 78

ABUTMENT PLAN SLAB REMOVED SOUTHWEST ABUTMENT

SCALE 3/16"=1'-0"

ABUTMENT PLAN SLAB REMOVED SOUTHEAST ABUTMENT

SCALE 3/16"=1'-0"

SLAB PLAN

SOUTHWEST ABUTMENT (AS SHOWN)
SOUTHEAST ABUTMENT (TO OPP. HAND)

SCALE: 3/16"=1'-0"

ELEVATION DD (AS SHOWN)
ELEVATION D'D' (OPPOSITE HAND)

SCALE: 3/16"=1'-0"

SECTION B-B

SCALE: 3/8"=1'-0"

NOTE:
SWA denotes Southwest Abutment
SEA denotes Southeast Abutment

PILE PLAN SOUTHWEST ABUTMENT

SCALE: 1/8"=1'-0"

END ELEVATION

SCALE: 3/8"=1'-0"

PILE PLAN SOUTHEAST ABUTMENT

SCALE: 1/8"=1'-0"

SECTION C-C

SCALE: 1/4"=1'-0"

NOTE:
For Parapet Reinforcing See Sheet No. 51

SECTION A-A

SCALE: 3/8"=1'-0"

Pile No.	Pile Tip Elevations S.W. Abut.	S.E. Abut.
1	748.98	749.75
2	750.22	750.21
3	749.82	752.25
4	751.84	751.58
5	749.74	748.66
6	750.62	752.39
7	749.07	751.83
8	750.30	751.42
9	748.23	749.83
10	750.05	749.07
11	748.90	747.91
12	751.60	751.74
13	748.74	750.08
14	751.19	752.07
15	744.57	749.75
16	750.67	751.36
17	748.67	753.28
18	750.67	751.44
19	751.00	752.18
20	750.75	747.78
21	750.25	750.61
22	750.00	747.69
23	747.67	747.36

STRUCTURE NO. 7

NOTES

For General Notes, see Sheet 50.
For Concrete Notes, see Sheet 35.
Max. Pile Load = 40 Tons

NO.	REVISION	BY	DATE
2	Deck Extensement & Widening, See RMP-49-84-10		1984
1	As Built		10/18/86

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER RT. 10 RAMP
S.W. & S.E. ABUTMENTS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A. | CHECKED: I.E., A.A. | DATE: 4-24-53
DRAWN: A. VINITSKY | IN CHARGE: O.A. | SCALE: AS NOTED

CONTRACT NO. C-22 SHEET 53 OF 78

Pile No.	Pile Tip Elevations Pier No. 1	Pier No. 2
1	750.83	749.25
2	750.62	751.83
3	748.67	749.00
4	750.45	752.15
5	749.25	751.91
6	750.13	751.67
7	749.42	749.42
8	750.70	751.59
9	749.00	750.42
10	*746.00	752.00
11	748.53	752.80
12	748.83	751.50
13	750.38	752.32
14	750.17	751.75
15	750.70	750.06
16	748.91	750.50
17	750.38	752.97
18	750.75	749.08

*= Test Pile used as Service Pile.

PLAN
WESTBOUND LANE PIER

All piles are 10 BP 42

NOTE: Elevations to bottom of masonry plate given on Framing Plan, Sheet 51

PLAN
EASTBOUND LANE PIER

ELEVATION
WESTBOUND LANE PIER

ELEVATION
EASTBOUND LANE PIER

SECTION B-B

SECTION A-A
SCALE: 1/2 IN. = 1 FT.

SECTION C-C
SCALE: 1/2 IN. = 1 FT.

SECTION D-D
SCALE: 1/2 IN. = 1 FT.

SECTION E-E
SCALE: 1/2 IN. = 1 FT.

	PIER NO.	DIMENSIONS F1	F2	F3	G	R	I	J	K	L	M1	M2	REINFORCEMENT a	b	c	d	e	g	i	j	k	m	n		h
WESTBOUND LANE	Pier 1	90°	—	—	3'-3"	4'-4"	13'-0"	38'-0"	11'-6½"	3'-0"	7'-3¼"	—	4-1¼"□	6-1¼"□	8-1¼"□	56-1¼"□	1"Φ@6"	1"Φ@9"	3/8"Φ@8"	3/8"Φ@8"	1"Φ@6"	1"Φ@9"	32-⅝"Φ		56-1¼"□
	Pier 2	do	—	—	do	do	do	do	11'-6½"	do	7'-3¼"	—	do.	do.	do.	do.	do.	do	do	do	do	do	do.		do.
EASTBOUND LANE	Pier 3	do	89°21'31"	88°43'03"	do	4'-5"	do	61'-0"	14'-1½"	do	7'-1¼"	7'-11"	do.	do.	do.	96-1¼"□	1"Φ@6½"	1"Φ@9½"	do	do	1"Φ@6"	1"Φ@9½"	60-⅝"Φ		96-1¼"□
	Pier 4	do	do	do	do	4'-4"	do	60'-0"	13'-9¾"	do	7'-1¼"	7'-5½"	do.	do.	do.	do.	do.	do	do	do	do	do	do.		do.

Pile No.	Pile Tip Elevations Pier No. 3	Pier No. 4
1	749.83	749.25
2	752.24	752.56
3	750.75	752.50
4	751.91	751.83
5	749.83	750.83
6	752.24	753.29
7	751.33	751.75
8	750.75	749.42
9	750.94	751.19
10	750.00	749.75
11	751.50	751.35
12	750.59	751.17
13	751.50	750.86
14	751.33	751.00
15	750.59	751.25
16	751.92	750.13
17	751.84	751.75
18	751.50	750.86
19	750.59	751.50
20	752.24	751.67
21	750.17	752.00
22	750.75	750.83
23	751.50	750.45
24	751.17	747.75
25	752.24	752.07
26	750.59	752.59
27	752.07	750.13
28	750.17	750.42

STRUCTURE NO. 7

NOTES
For General Notes see Sheet 50
For Concrete Notes see Sheet 35.
Maximum Pile Load = 40 Tons

NO.	REVISION	BY	DATE
2	DECK REPLACEMENT; WORKING, SEE EMP. 43-81-0		1984
1	AS BUILT		10/8/56

OHIO TURNPIKE COMMISSION
OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER RT. 10 RAMP
PIERS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O. A. CHECKED: I. E., A. A. DATE: 4-24-53
DRAWN: W. A. B. IN CHARGE: O. A. SCALE: 1/4 IN. & AS NOTED

CONTRACT NO. C-22 SHEET 54 OF 78

PLAN
SCALE: 1" = 20'

ROUTE 10 PROFILE
EDGE OF MALL WESTBOUND LANE
SCALE: VERTICAL 1" = 5 FT.
HORIZONTAL 1" = 25 FT.

LOCATION PLAN
SCALE: 1" = 500 FT.

SECTION A-A
SCALE: 1" = 10'

SECTION B-B
SCALE: 1" = 10'

GENERAL NOTES

Design in accordance with Design Specifications for Highway Structures, State of Ohio, Oct. 1, 1951.
Predicted frequency per lane of 2000.
Superstructure: Concrete slab on WF stringers.
Substructure: Piers on spread footings.
Abutments on steel bearing piles.
All elevations refer to Mean Sea Level Datum as established by U.S. Coastal and Geodetic Survey.
For details of borings, see Master Soil Profile, Contract C-22, and respective laboratory logs in book entitled "Ohio Turnpike Project No. 1 Subsurface Exploration Logs, Contract C-22."

REFERENCE DRAWINGS

Framing Plan	Sheet 56
Abutments	Sheets 57 & 58
Piers	Sheet 59
Handrail Details	Std. Dwg. No. 5.
Drainage Details	Std. Dwg. No. 15.
Guard Rail Details	Std. Dwg. No. 17.

ELEVATION
SCALE: 1" = 20 FT

LONGITUDINAL SECTION
SCALE: 1" = 20'

SUMMARY OF QUANTITIES

ITEM NO.	DESCRIPTION	UNIT	ABUT.	PIERS	SUPERSTR.	GENERAL	TOTAL
E-2	Excavation for structures	Cu. Yd.	454.8	813.7			1268.5
S-1	Concrete for structures - Class C	Cu. Yd.	413.8	580.4	494.8		1488
S-4	Reinforcing Steel	Pounds	30,[illegible]	[illegible]	126,[illegible]		[illegible]
S-7	Structural Steel	Pounds			473,902		473,902
S-9	Structural Expansion Joints, and/or Contraction Joints.	Pounds			23,877		23,877
S-14	Railing Type "A"	L.F.			765.3		765.3
S-16	First Test Pile	Each	1				1
S-17	Pile Test Load	Each					0
S-18	Furnishing Steel Bearing Piles 10 BP 42	L.F.					
S-18	Driving Steel Bearing Piles " "	L.F.	2791.9				2791.9
S-18	Splices for Steel Bearing Piles " "	Each					0
S-29	Drainage of Structure - Scuppers - Type "A"	Each			4		4
S-29	Drainage of Structure - 6" W.I. Pipe	L.F.				110.7	110.7
S-29	Drainage of Structure - 6" Pipe	L.F.				68	68
I-15	Guard Rail Type "A"	L.F.			762.6		762.6
I-24	Delineators	Each			4		4

STRUCTURE NO. 8

NO.	REVISION	BY	DATE
2	Deck Replacement & Widening, See EMP 45-84-10		1984
1	As Built		

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER ROUTE 10
GENERAL PLAN & SECTIONS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A. | CHECKED: I.E., A.A. | DATE: 4-24-53
DRAWN: I.H. | IN CHARGE: O.A. | SCALE: AS NOTED

CONTRACT NO. C-22 SHEET 55 OF 78

NOTE:
N.W.A. DENOTES NORTH WEST ABUTMENT
N.E.A. " NORTH EAST "
S.W.A. " SOUTH WEST "
S.E.A. " SOUTH EAST "

NOTE: ELEVATIONS SHOWN ARE AT BOTTOM OF MASONRY PLATE.

FRAMING PLAN

DECK CROSS SECTION WEST BOUND LANE
SCALE: 1/2 IN. = 1 FT.

Note: For details of parapet, see Sh. 51.

DECK CROSS SECTION EAST BOUND LANE
SCALE: 1/2 IN. = 1 FT.

DETAIL OF WEB SPLICE
SCALE: 1/2 IN. = 1 FT.

DETAIL OVER EXPANSION PIER INTERIOR STRINGERS
SCALE: 1/2 IN. = 1 FT.

DETAIL OVER ABUTMENT
SCALE: 1/2 IN. = 1 FT.

DETAIL OVER EXPANSION PIER EXTERIOR STRINGERS
SCALE 1/2 IN. = 1 FT.

DETAIL OVER FIXED PIER
SCALE: 1/2 IN. = 1 FT.

CAMBER DIAGRAM FOR STRINGERS
FOR DEAD LOAD AND VERTICAL CURVE

PLAN A
SCALE 1/2 IN. = 1 FT.

NOTES
For General Notes See Sheet 55
For Structural Steel Notes See Sheet 34
For Concrete Notes See Sheet 35
For Parapet Reinforcing See Sheet 51
For Roadway Expansion Joints & Fixed Joints See Sheet 63

STRUCTURE NO. 8

NO.	REVISION	BY	DATE
2	Deck Replacement & Widening. See RMP. 43-84-10		1984
1	As Built		10/8/86

OHIO TURNPIKE COMMISSION

OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER RT. 10
FRAMING PLAN

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A.	CHECKED: I.E., A.A.	DATE: 4-24-53
DRAWN: W.A.	IN CHARGE: O.A.	SCALE: AS NOTED

CONTRACT NO. C-22 SHEET 56 OF 78

PLAN
SLAB REMOVED
NORTHWEST ABUTMENT
SCALE: 3/16"=1'-0"

PLAN
SLAB REMOVED
NORTHEAST ABUTMENT
SCALE: 3/16"=1'-0"

SECTION A-A
SCALE: 3/8"=1'-0"

NOTE-
N.W.A. denotes north-west abutment
N.E.A. denotes north-east abutment

SECTION B-B
SCALE: 3/8"=1'-0"

NOTE:
ALL PILES TO BE 10 B.P. 42

PILE PLAN
NORTHWEST ABUTMENT (AS SHOWN)
NORTHEAST ABUTMENT (TO OPP. HAND)
SCALE: 1/8"=1'-0"

Pile Tip Elevations					
Pile No.	NE. Abut.	NW. Abut.	Pile No.	NE. Abut.	NW. Abut.
1	762.42	759.45	13	* 761.42	759.70
2	763.24	760.96	14	763.33	761.12
3	762.25	760.62	15	763.83	761.37
4	763.24	760.96	16	763.00	761.38
5	762.91	760.87	17	763.00	761.30
6	763.00	761.44	18	763.87	761.47
7	762.25	762.62	19	763.75	761.63
8	764.01	762.74	20	763.87	761.63
9	763.25	762.04	21	——	761.63
10	763.81	761.44	22	——	761.63
11	762.25	759.37	23	——	761.55
12	763.41	761.53			

* = Test Pile used as Service Pile.

END ELEVATION
SCALE: 3/8"=1'-0"

SECTION D-D
SCALE: 3/8"=1'-0"

NOTES
For Concrete Notes see Sheet 35.
For General Notes see Sheet 55.
Max. Pile Load = 40 Tons.

ELEVATION C-C (AS SHOWN)
ELEVATION C'-C' (OPPOSITE HAND)
SCALE: 3/16"=1'-0"

PLAN OF ABUTMENT SLAB
SCALE: 3/16"=1'-0"

STRUCTURE NO. 8

NO.	REVISION	BY	DATE
2	Deck Replacement & Widening, See RMP. 49-84-10		1984
1	As Built		10/18/54

OHIO TURNPIKE COMMISSION
OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER ROUTE 10
N.W. & N.E. ABUTMENTS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A. | CHECKED: I.E., A.A. | DATE: 4-24-53
DRAWN: MARINO | IN CHARGE: O.A. | SCALE: AS NOTED

CONTRACT NO. C-22 SHEET 57 OF 78

ABUTMENT PLAN - SLAB REMOVED
WEST ABUTMENT
SCALE: 3/16 IN. = 1 FT.

SECTION B-B
SCALE: 3/8 IN. = 1 FT.

NOTE -
S.W.A. denotes south-west abutment.
S.E.A. denotes south-east abutment

ELEVATION C-C
ELEVATION C'-C' (OPPOSITE HAND)
SCALE: 3/16 IN. = 1 FT.

NOTE:
FOR PARAPET REINFORCING SEE SHEET No. 51

SECTION A-A
SCALE: 1/4 IN. = 1 FT.

Pile Tip Elevations					
Pile No.	S.E. Abut.	S.W. Abut.	Pile No.	S.E. Abut.	S.W. Abut.
1	762.24	759.54	11	761.79	759.54
2	762.67	759.65	12	763.77	760.14
3	762.24	759.45	13	762.72	759.37
4	763.10	759.97	14	763.93	759.90
5	761.16	759.45	15	763.64	760.07
6	764.06	760.30	16	763.68	760.07
7	762.72	759.37	17	764.02	760.15
8	761.95	760.14	18	—	759.98
9	763.66	759.45	19	—	759.98
10	763.79	761.43	20	—	759.90

END ELEVATION
SCALE: 3/8 IN. = 1 FT.

PILE PLAN
SCALE: 1/8 IN. = 1 FT.

NOTES
For General Notes see Sheet 55.
For Concrete Notes see Sheet 35.
Max. Pile Load = 40 Tons

ABUTMENT PLAN - SLAB REMOVED
EAST ABUTMENT
SCALE: 3/16 IN. = 1 FT.

SECTION D-D
SCALE: 1/4 IN. = 1 FT.

SLAB PLAN
SCALE: 3/16 IN. = 1 FT.

STRUCTURE NO. 8

NO.	REVISION	BY	DATE
2	DECK REPLACEMENT & WIDENING, SEE EMP. 43-84-10		1984
△	AS BUILT		10/18/56

OHIO TURNPIKE COMMISSION
OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER ROUTE 10
S.W. & S.E. ABUTMENTS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A.	CHECKED: I.E., A.A.	DATE: 4-24-53
DRAWN: W.A.B.	IN CHARGE: O.A.	SCALE: AS NOTED

CONTRACT NO. C-22 SHEET 58 OF 78

PLAN
WESTBOUND LANE PIER

NOTE- Elevations to bottom of Masonry Plate given on Framing Plan Sh. 56.

PLAN
EASTBOUND LANE PIER

SECTION C-C
SCALE: 1/2 IN.=1 FT.

SECTION D-D
SCALE: 1/2 IN.=1 FT.

SECTION E-E

ELEVATION
WESTBOUND LANE PIER

ELEVATION
EASTBOUND LANE PIER

SECTION B-B

SECTION A-A
SCALE: 1/2 IN.=1 FT.

NOTES

For general notes see sheet 55
For concrete notes see sheet 35
Maximum Soil Bearing Pressure = 3 Tons/sq. ft.

	PIER NO.	ELEV OF FOOTING	TOP OF PIER ELEV. X	TOP OF PIER ELEV. Y	DIMENSIONS F1	F2	F3	G	I	J	K	L	M1	M2	REINFORCEMENT a	b	c	d	e	f	g	h	i	l	m	n	j
WESTBD. LANE	Pier 1	777.00	799.50	800.50	72°36'26"	74°10'30"	75°44'52"	3'-0"	10'-0"	60'-0"	13'-11½"	3'-0"	7'-5⅞"	6'-6¾"	4-1¼□	6-1¼□	8-1¼□	96-1¼□	16-1¼□	13-1¼□	16-1¼□	96-1¼□	3/8"φ @ 8"	72-⅞φ	36-⅝φ	60-⅝φ	3/8"φ @ 8
	Pier 2	777.00	800.00	800.96	do	do	do	do	do	57'-0"	13'-0⅛"	do	do	5'-3½"	do.	do.	do.	do.	do	do	do	do.	do	68-⅞φ	34-⅝φ	54-⅝φ	do
	Pier 3	777.00	800.00	801.43	do	do	do	do	do	55'-0"	12'-1½"	do	do	3'-9¼	do.	do.	do.	do.	do	do	do	do	do	66-⅞φ	33-⅝φ	54-⅝φ	do
EASTBD. LANE	Pier 4	777.00	798.98	799.84	do	71°55'01"	71°08'57"	do	do	51'-0"	10'-10⅝"	do	7'-0⅛	6'-7½"	do.	do.	do.	96-1¼□	do	do	do	96-1¼□	do	61-⅞φ	30-⅝φ	48-⅝φ	do
	Pier 5	777.00	799.55	800.38	do	do	do	do	do	49'-0"	10'-4⅞"	do	do	6'-0¼"	do.	do.	do.	do.	do	do	do	do.	do	59-⅞φ	30-⅝φ	42-⅝φ	do
	Pier 6	777.00	800.18	800.98	do	do	do	do	do	48'-0"	10'-0"	do	do	5'-3¾"	do.	do.	do.	do.	do	do	do	do.	do	58-⅞φ	29-⅝φ	do.	do

STRUCTURE NO. 8

NO.	REVISION	BY	DATE
2	Deck Replacement & Widening, See RMP 45-84.10		1984
1	As Built		10/8/86

OHIO TURNPIKE COMMISSION
OHIO TURNPIKE PROJECT NO. 1

TURNPIKE BRIDGE OVER ROUTE 10
PIERS

KNAPPEN - TIPPETTS - ABBETT - McCARTHY
CONTRACTING ENGINEER
DESIGN SECTION D-7

DESIGNED: O.A. DRAWN: A.M.D. CHECKED: I.E., A.A. IN CHARGE: O.A. DATE: 4-24-53 SCALE: 1/4 IN. = 1 FT. AS NOTED

CONTRACT NO. C- 22 SHEET 59 OF 78